

PETROBLOK 100

Aqueous Silicone-based solution used for the impregnation of mineral construction material to make them water repellent

KTISIS

*Davari and Christodoulou Street
19002 Paiania
Athens, GREECE
Telephone: +30 210 6646587 (Athens)
www.ktisis.eu
email: akis@ktisis.eu*

TECHNICAL DATA

Colour	Transparent
Density	1,05 g/cm ³
pH-value	13-14 at 20o C

TECHNICAL INFORMATION

Petroblok 100 is supplied as a ready to use liquid. The material can be applied with a brush, a roller or an airless spray.

APPLICATION FIELDS

- clay products such as roof tiles, bricks, flower pots
- masonry products such as stone houses, walls, bridges and other constructions
- porous concrete
- tile joints
- gypsum and gypsum based fibre boards

STORAGE AND SAFETY PRECAUTIONS

Petroblok should always be stored in the tightly closed original container. Always wear gloves and glasses when handling the material.

Further technical information, as well as multimedia material regarding waterproofing can be accessed at the KTISIS website.

<http://www.ktisis.eu/>

Disclaimer: All guidelines described here are subject to the responsibility of the persons who undertake the application of the materials. KTISIS is unable to provide any warranty for the products, since the we cannot be aware of the conditions (temperature, humidity, substrate quality etc) as well as the application methods that prevail for each individual project.

